



WORK AREA (...Continued)

- If you let go of the handle when the engine fires up, do not try to grab it. Stop the engine using the stop control. Then start the engine again.
- Never stop the engine using the decompression lever. This may damage the engine and will be regarded as misuse by the hire company. Only use the correct engine STOP control.

HYDRAULIC SAFETY

- Hydraulic oil can be hazardous, keep it away from eyes and mouth, wash it off your skin immediately.
- The hydraulic system has been checked and topped up by the hire company. You only need to check the hydraulic oil level by looking at the sight glass. If the oil level is low contact the hire company.
- If you get hydraulic oil on your clothes change them immediately.
- The hydraulic oil is pressurized to over 120 psi (80 bar). Do not attempt any repair or adjustment.
- Do not try to stop a leak by pressing a thumb over it. Hydraulic oil under pressure can penetrate the skin with serious results. It is also very hot. Keep clear of leaks.

USING THE HYDRAULIC BREAKER

- Wear your protective equipment including ear defenders and safety boots.
- Do not operate the breaker until the tool is on the work surface. Do not operate the breaker if the tool has no load.

- At the start of each breaking operation, position the breaker at right angles to the work surface. This will prevent the tool skating across the surface to be broken when you operate the breaker.
- Do not use the breaker as a lever to prise open the work area.
- Do not try to lever free a tool jammed in the work surface. Instead release the tool from the breaker and insert another one. Use this second tool to break up the ground and free the first tool.
- Keep the hydraulic hoses clear of your work area.
- Do not stretch the hoses as you extend your work area, move the power pack.
- Do not drag the power pack by pulling on the hoses.
- If you think a hose is damaged or leaking, stop work, stop the engine and release the pressure by moving the flow control lever to a minimum and squeezing the trigger on the breaker.
- Watch out for signs that vibration may be affecting your hands. If your fingers start to tingle or feel numb, take a short break from using the breaker. Exercise your fingers to encourage blood circulation.
- To help prevent vibration affecting your hands, operate the machine for shorter periods. Keep your hands warm – wearing gloves may help do this.
- Stop the engine before leaving the equipment unattended.
- If you think the equipment is faulty, or does not work properly do not attempt to repair it, contact the hire company.

Please keep this leaflet safely as it may be required for future reference



Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Soliuhull B37 7YE

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

Hydraulic Breaker

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read all of this leaflet BEFORE you use the Hydraulic Breaker

- Plan your work and think ahead to make sure you will always be working safely.
- Diesel fuel is flammable. Take care not to cause a fire or explosion.
- This hydraulic breaker is designed for breaking concrete, stone, tarmac and similar surfaces.
- The action of this hydraulic breaker can cause injury or damage if the machine is not used in a careful and controlled way.
- If you have not used a hydraulic breaker before, familiarise yourself with the machine on some straightforward work before you start on the main task.
- You must have at least the following items of personal protective equipment: goggles: impact resistant EN166 – B or BS2092 grade 1; ear muffs or plugs giving protection from levels up to 110 dB(A); safety boots to EN345 or BS1870/4972; Dust mask – a minimum of EN149 FFP3(s) protection; gloves.
- This machine must not be used by minors, or by anyone under the influence of drugs or alcohol.
- This hydraulic breaker is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.

WORK AREA

- Do not use this power pack where there is a danger of explosion. It will ignite fumes from petrol, or gas cylinders.
- Using this equipment indoors or in confined spaces could cause fatal carbon monoxide poisoning. Never use it in domestic premises and only use it in other indoor situations if its suitability and the ventilation required has been fully assessed. Mechanical extraction ventilation will almost always be required.
- Make sure that the area is clear and safe and that no-one is near to you or could distract you.



(Continued overleaf...)



Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting material is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Soliuhull B37 7YE



©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

- Hand start
- If the engine is warm, there is no need to started by hand. This can be hazardous, take care.
- If the machine has a fuel valve, open it.
- Move the engine RUN/STOP control to the RUN position.
- Set the flow control lever on the operating panel to 'MIN' position.
- Stand by the engine and find the starting handle and the decompression lever.
- Do not wear gloves when you start the engine. Also, make sure that you have no loose clothing or flapping sleeves that could become entangled.
- Fit the starting handle to the shaft, and check by turning it anti-clockwise that the ratchet mechanism works. Check the starting handle to the shaft, and check by turning it anti-clockwise that the ratchet mechanism works. Check the starting handle to the shaft, and check by turning it anti-clockwise that the ratchet mechanism works.
- Also that the handle slides on and off the shaft easily.
- Move the decompression lever into the decompression position.
- If the engine is fitted with a cold start button, press it in when starting from cold.
- Grasp the starting handle firmly in one hand – but do not wrap your thumb around the handle. Keep it on the same side as your fingers – this is very important. Your thumb could be broken if you wrap it around the handle, and the engine kicks back.
- Crank the engine strongly before lowering the decompression lever smoothly. The engine should fire up. If it doesn't, go through the steps again from instruction 15 above.
- If the engine is now running, slide the handle off the shaft. Slow the handle safely.

- your work area.
- Clean the filler cap and the area around it to prevent dirt falling into the fuel tank.
- Use a funnel and clean diesel when refuelling. Do not spill any fuel on yourself or the machine.
- Wipe any fuel off the machine.
- Dispose of fuel soaked cloth carefully.
- If you spill any fuel on your clothes, change them straight away.
- Put all fuel caps back on properly, and move your fuel cap to a safe, cool place.
- Electric start
- Check the cold start device for a little secods look to see if there is any smoke coming from the exhaust. If there is, try to reengage the cold start device for about twenty seconds then engage the starter.
- If the machine has a fuel valve, open it.
- Set the flow control lever on the operating panel to 'MIN' position.
- Set the START/STOP switch to START and engage the cold start device for about twenty seconds then engage the starter.
- Check the oil and fuel levels before you continue.
- Do not attempt to uncouple the hydraulic hoses while the system is pressurised. Stop the engine and release the pressure by moving the flow control lever to minimum and squeezing the trigger on the breaker.
- Do not allow the disconnected hydraulic hose couplings to become dirty, keep them clean.
- No smoking.
- Stop the engine and let it cool down.
- If possible move the machine away from 'max' position while working.



Before Starting Work...

- The following items of personal protective equipment (ppe) are the minimum that should be worn whenever you use this hydraulic breaker. Particular jobs or environments may require a higher level of protection.
- You must wear impact resistant goggles (EN166 – B or BS2092 grade 1) when you are working with this hydraulic breaker.
- This hydraulic breaker is likely to cause noise levels up to 110 dB(A) – wear appropriate ear muffs or plugs giving hearing protection for this level as a minimum.
- You must wear safety boots (EN345 or BS1870/4972).
- Anybody who is working near to you will also need to wear appropriate personal protective equipment.
- Check all your equipment, including hoses, power pack and the breaker. Do not use anything found damaged - contact the hire company.
- Check that the hoses have no cuts, abrasions, or bulges in them.
- Check that the quick release, self-sealing hose couplings are clean before connecting them.
- Check that the power pack is sited firmly and safely near to your work area.
- Check engine oil and fuel levels each day before starting work. Check levels more often if the breaker is used continuously.
- The flow control lever should be set to 'max' position while working.

OPERATORS

The hydraulic breaker may damage pipes or cables buried under the surface.

WORK AREA (...Continued)