

HD 8 VV

Tandem roller with two vibrating roller drums

Tandem rollers Series HD CompactLine / Series H199




HIGHLIGHTS HD CompactLine

- > Optimum front view due to concaving front end
- > Modern instrument panel
- > Low machine height
- > 3-point swivel joint for optimum driving comfort
- > Central suspension point
- > Clear Side — one-sided drum suspension
- > Low working platform, high stability










Machine dimensions

Total length (L)	mm	2260
Width (B)	mm	856
Total height (H)	mm	2210
Drum width (X)	mm	800/800
Height loading, min. (Hl)	mm	1580



EPA Tier 4

TECHNICAL DATA		Unit	HD 8 VV
	Weights		
	Operating weight with ROPS	kg	1580
	Operating weight, max.	kg	1840
	Static linear load, front/rear	kg/cm	9,6/10,2
	Machine dimensions		
	Total length	mm	2260
	Total height with ROPS	mm	2210
	Height loading, min.	mm	1580
	Total width	mm	856
	Wheel base	mm	1560
	Max. working width	mm	856
	Turning radius, inside	mm	2230
	Drum dimensions		
	Drum width, front/rear	mm	800/800
	Drum diameter, front/rear	mm	620/620
	Drum thickness, front/rear	mm	12/12
	Drum type, front		smooth/non-divided
	Drum type, rear		smooth/non-divided
	Diesel engine		
	Manufacturer		KUBOTA
	Version		D1005
	Number of cylinders		3
	Power rat. ISO 14396, kW/PS/rpm		14,8/20,1/2700
	Power rating SAE J1349, kW/HP/rpm		14,8/19,8/2700
	Emissions standard EU/USA		EPA Tier 4
	Drive		
	Speed, infinitely variable	km/h	0 - 11,0
	Climbing ability, vibration on/off	%	30/40
	Vibration		
	Vibration frequency, front, I/II	Hz	65/52
	Vibration frequency, rear, I/II	Hz	65/52
	Amplitude, front, I/II	mm	0,50/0,50
	Amplitude, rear, I/II	mm	0,50/0,50
	Centrifugal force, front, I/II	kN	25/16
	Centrifugal force, rear, I/II	kN	25/16
	Steering		
	Oscillation angle +/-	°	8
	Steering, type		Articulated steering
	Sprinkler system		
	Water sprinkler, type		Pressure
	Tank capacity/Fill capacity		
	Fuel tank, capacity	L	33
	Water tank, capacity	L	70
	Sound level		
	Acoustic power LW(A), sticker		104
	Acoustic power LW(A), measured		104

EQUIPMENT

3-point articulation, Dashboard with displays, indicator lights and switches, Dashboard cover, lockable and weather-resistant, Handrails, Battery isolation switch, Clear Side, Pressure water sprinkling with interval switch, Operator's platform with entry from both sides, Hydrostatic steering, Vibration-isolated operator's platform, Vibration front and rear, switchable single and doubled, Central lifting bracket

OPTIONAL EQUIPMENT

Working lights, Back-up alarm (reversing), Battery isolator switch with cable activation, Driver's seat with seat heating, black imitation leather, comfort equipment, Additional drive lever, left, Anti-freeze injection system, ROPS, foldable, Rotating beacon, Water drain valve, V-belt protection, Plastic scraper, foldable, Automatic engine-off function, WIFMS fleet management interface, Tow eye, at the front, Cup holder

HAMM AG

Hammstraße 1
D-95643 Tirschenreuth
Tel. +49 9631 80-0
Fax +49 9631 80-111
www.hamm.eu



HAMM